

**Description**

Fastener Length: 17/32", Thread: 10-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1223C3L                                |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5306-00-903-7179                          |
| Schedule B:             | 7318.15.2091                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS1223C3L Specifications

|  |  |
|--|--|
| <b>Thread Class:</b>                         | 3a   |
| <b>Thread Direction:</b>                     | Right-hand   |
| <b>Thread Length:</b>                        | 0.313 Inches Minimum And 0.363 Inches Maximum              |
| <b>Fastener Length:</b>                      | 0.511 Inches Minimum And 0.541 Inches Maximum              |
| <b>Head Style:</b>                           | Dished Hexagon   |
| <b>Head Height:</b>                          | 0.110 Inches Minimum And 0.125 Inches Maximum              |
| <b>Width Between Flats:</b>                  | 0.367 Inches Minimum And 0.376 Inches Maximum              |
| <b>Locking Feature:</b>                      | Strip Threads  |
| <b>Nominal Thread Diameter:</b>              | 0.190 Inches   |
| <b>Grip Length:</b>                          | 0.178 Inches Minimum And 0.198 Inches Maximum              |
| <b>Features Provided:</b>                    | Finished Head  |
| <b>Thread Quantity Per Inch:</b>             | 32   |
| <b>Minimum Tensile Strength:</b>             | 140000 Pounds Per Square Inch                              |
| <b>Material:</b>                             | Iron Alloy 660 Overall                                     |
| <b>Material Document And Classification:</b> | Ams 5732 Assn Std Single Material Response Overall         |
| <b>Thread Series Designator:</b>             | Unf  |
| <b>Specification/standard Data:</b>          | 80205-nas1223 Professional/Industrial Association Standard |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1223C3L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.