

Description

Fastener Length: 21/32", Thread: 10-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS1223C5 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-01-548-2249 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |

NO IMAGE
AVAILABLE

P/N NAS1223C5 Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.338 Inches Nominal |
| Fastener Length: | 0.635 Inches Minimum And 0.665 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.110 Inches Minimum And 0.125 Inches Maximum |
| Width Between Flats: | 0.367 Inches Minimum And 0.376 Inches Maximum |
| Grip Diameter: | 0.1890 Inches Minimum And 0.1895 Inches Maximum |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.302 Inches Minimum And 0.325 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 140000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| Material: | Steel Corrosion Resisting Overall |
| Material Document And Classification: | Ams5735 Assn Std 1st Material Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1223C5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.