

## P/N NAS1224-10

### **Description**

Thread: 1/4-28, Thread Length: 3/8"

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS122410

Minimum Qty (MOQ): 5 EA

NSN: 5306-00-948-4061

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS1224-10 Specifications**

| Thread Class:                                  | 3a  |
|--|---|
| Thread Direction:                              |   |
|  | Right-hand  |
| Thread Length:                                 | 0.400 Inches Minimum And 0.450 Inches Maximum   |
| Fastener Length:                               | 1.035 Inches Minimum And 1.065 Inches Maximum   |
| Head Style:                                    | Dished Hexagon  |
| Head Height:                                   | 0.125 Inches Minimum And 0.140 Inches Maximum   |
| Width Between Flats:                           | 0.430 Inches Minimum And 0.439 Inches Maximum   |
| Locking Feature:                               | Patch Threads Or Pellet Threads Or Strip Threads  |
| Grip Diameter:                                 | 0.2485 Inches Minimum And 0.2495 Inches Maximum   |
| Nominal Thread Diameter:                       | 0.250 Inches  |
| Grip Length:                                   | 0.615 Inches Minimum And 0.635 Inches Maximum   |
| Thread Quantity Per Inch:                      | 28  |
| Minimum Tensile Strength:                      | 160000 Pounds Per Square Inch   |
| Hardness Rating:                               | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall   |
| Material:                                      | Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall  |
| Material Document And Classification:          | Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall |
| Surface Treatment:                             | Cadmium Overall And Chromate Overall  |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall   |
| Thread Series Designator:                      | Unjf  |
| Specification/standard Data:                   | 80205-nas1224 Professional/industrial Association Standard  |

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/shear+bolts/NAS1224-10">https://military-fasteners.com/bolts/shear+bolts/NAS1224-10</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/shear+bolts/NAS1224-10">https://military-fasteners.com/bolts/shear+bolts/NAS1224-10</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/shear+bolts/NAS1224-10">https://military-fasteners.com/bolts/shear+bolts/NAS1224-10</a> and selecting the quantity you want then click "add to cart".