

P/N NAS1224-11L

Description

Fastener Length: 1-1/8", Thread: 1/4-28, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS122411L

Minimum Qty (MOQ): 10 EA

NSN: 5306-01-123-9779

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1224-11L Specifications

Thread Direction: Right-hand Thread Direction: 0.400 Inches Minimum And 0.450 Inches Maximum Fastener Length: 1.098 Inches Minimum And 1.128 Inches Maximum Head Style: Dished Hexagon Head Height: 0.125 Inches Minimum And 0.140 Inches Maximum Width Between Flats: 0.430 Inches Minimum And 0.439 Inches Maximum Locking Feature: Peller Threads Or Strip Threads Or Patch Threads Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Nominal Thread Diameter: 0.678 Inches Minimum And 0.698 Inches Maximum Nominal Thread Quantity Per Inch: 28 Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 28 Burface Finish: 30.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 30.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Surface Finish: 33.0 Microinches Threads Surface Finish: 35.0 Microinches Bearing Surface Of Head Material: 25cel Comp £340 Fastener Or Steel Comp £740 Fastener Or Stee		
Thread Length: 0.400 Inches Minimum And 0.450 Inches Maximum Fastener Length: 1.098 Inches Minimum And 1.128 Inches Maximum Head Style: Dished Hexagon Head Height: 0.125 Inches Minimum And 0.140 Inches Maximum Width Between Flats: 0.430 Inches Minimum And 0.439 Inches Maximum Locking Feature: Pellet Threads Or Strip Threads Or Patch Threads Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Nominal Thread Diameter: 0.250 Inches Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Baring Surface Of Head Material: Plastic Polyamide Locking Feature Material: Steel Comp E4340 Fastener Or Steel Comp 4140 Fastener Or Steel Comp 8740 Fastener Or Steel Comp 8735 Fastener Or Steel Comp 6150 Fastener Surface Treatment: Occupied Teatment Procument And Classification: Qn-p-416 Type 2 Class 2 Fed Spec Single Treatment Response Fastener Turked Seri	Thread Class:	3a
Fastener Length: 1.098 Inches Minimum And 1.128 Inches Maximum Head Style: Dished Hexagon Head Height: 0.125 Inches Minimum And 0.140 Inches Maximum Width Between Flats: 0.430 Inches Minimum And 0.439 Inches Maximum Locking Feature: Pellet Threads Or Strip Threads Or Patch Threads Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Nominal Thread Diameter: 0.578 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Fineads Surface Finish: 32.0 Microinches Bearing Surface Of Head Material: Plastic Polyamide Locking Feature Material: 2520 Fed Speci Ed Satener Surface Treatment: Cadmium Fastener And Chromate Fastener Surface Treatment Document And Classification: Qn-p-416 Type 2 Class 2 Fed Spec Single Treatment Response Fastener Thread Series Designator: Unif	Thread Direction:	Right-hand
Head Style: Dished Hexagon Head Height: 0.125 Inches Minimum And 0.140 Inches Maximum Width Between Flats: 0.430 Inches Minimum And 0.439 Inches Maximum Locking Feature: Pellet Threads Or Strip Threads Or Patch Threads Grip Dameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Nominal Thread Diameter: 0.250 Inches Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Nominal Thread Diameter: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Bearing Surface Of Head Material: Plastic Polyamide Locking Feature Material: Steel Comp E4340 Fastener Or Steel Comp 4140 Fastener Or Steel Comp 8740 Fastener Or Steel Comp 6150 Fastener Surface Treatment: Cadmium Fastener And Chromate Fastener Surface Treatment Document And Classification: Unif	Thread Length:	0.400 Inches Minimum And 0.450 Inches Maximum
Head Height: 0.125 Inches Minimum And 0.140 Inches Maximum Width Between Flats: 0.430 Inches Minimum And 0.439 Inches Maximum Locking Feature: Pellet Threads Or Strip Threads Or Patch Threads Grip Dameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Nominal Thread Diameter: 0.250 Inches Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Surface Finish: 32.0 Microinches Bearing Surface Of Head Material: Plastic Polyamide Locking Feature Material: Surface Treatment: Cadmium Fastener And Chromate Fastener Surface Treatment Document And Classification: Thread Series Designator: Unjf	Fastener Length:	1.098 Inches Minimum And 1.128 Inches Maximum
Width Between Flats: 0.430 Inches Minimum And 0.439 Inches Maximum Locking Feature: Pellet Threads Or Strip Threads Or Patch Threads Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Nominal Thread Dlameter: 0.570 Inches Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Surface Finish: 32.0 Microinches Bearing Surface Of Head Material: Plastic Polyamide Locking Feature Material: 2tecl Comp E4340 Fastener Or Steel Comp 4140 Fastener Or Steel Comp 8740 Fastener Or Steel Comp 8735 Fastener Or Steel Comp 6150 Fastener Surface Treatment: Cadmium Fastener And Chromate Fastener Surface Treatment Document And Classification: Oq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response Fastener Thread Series Designator: Unjf	Head Style:	Dished Hexagon
Locking Feature:Pellet Threads Or Strip Threads Or Patch ThreadsGrip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumNominal Thread Diameter:0.250 InchesGrip Length:0.678 Inches Minimum And 0.698 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsSurface Finish:63.0 Microinches Bearing Surface Of HeadMaterial:Plastic Polyamide Locking FeatureMaterial:Steel Comp E4340 Fastener Or Steel Comp 4140 Fastener Or Steel Comp 8740 Fastener Or Steel Comp 8735 Fastener Or Steel Comp 6150 FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjf	Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Grip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumNominal Thread Diameter:0.250 InchesGrip Length:0.678 Inches Minimum And 0.698 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsSurface Finish:63.0 Microinches Bearing Surface Of HeadMaterial:Plastic Polyamide Locking FeatureMaterial:Comp E4340 Fastener Or Steel Comp 4140 Fastener Or Steel Comp 8740 Fastener Or Steel Comp 8735 Fastener Or SteelSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Oq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjf	Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Nominal Thread Diameter: 0.250 Inches Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Surface Finish: 63.0 Microinches Bearing Surface Of Head Material: Plastic Polyamide Locking Feature Material: Surface Treatment: Cadmium Fastener Or Steel Comp 4140 Fastener Or Steel Comp 8740 Fastener Or Steel Comp 8735 Fastener Or Steel Comp 6150 Fastener Surface Treatment Document And Classification: Thread Series Designator: Unjf	Locking Feature:	Pellet Threads Or Strip Threads Or Patch Threads
Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Surface Finish: 63.0 Microinches Bearing Surface Of Head Material: Plastic Polyamide Locking Feature Steel Comp E4340 Fastener Or Steel Comp 4140 Fastener Or Steel Comp 8740 Fastener Or Steel Comp 8735 Fastener Or Steel Comp 6150 Fastener Surface Treatment: Cadmium Fastener And Chromate Fastener Surface Treatment Document And Classification: Thread Series Designator: Unjf	Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Thread Quantity Per Inch: Minimum Tensile Strength: 160000 Pounds Per Square Inch 160000 P	Nominal Thread Diameter:	0.250 Inches
Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsSurface Finish:63.0 Microinches Bearing Surface Of HeadMaterial:Plastic Polyamide Locking FeatureMaterial:Steel Comp E4340 Fastener Or Steel Comp 4140 Fastener Or Steel Comp 8740 Fastener Or Steel Comp 8735 Fastener Or SteelSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjf	Grip Length:	0.678 Inches Minimum And 0.698 Inches Maximum
Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Surface Finish: 63.0 Microinches Bearing Surface Of Head Material: Plastic Polyamide Locking Feature Material: Steel Comp E4340 Fastener Or Steel Comp 4140 Fastener Or Steel Comp 8740 Fastener Or Steel Comp 8735 Fastener Or Steel Comp 6150 Fastener Surface Treatment: Cadmium Fastener And Chromate Fastener Surface Treatment Document And Classification: Unjf	Thread Quantity Per Inch:	28
Surface Finish: Surface Finish: 32.0 Microinches Grip 32.0 Microinches Threads Surface Finish: 63.0 Microinches Bearing Surface Of Head Material: Plastic Polyamide Locking Feature Material: Steel Comp E4340 Fastener Or Steel Comp 4140 Fastener Or Steel Comp 8740 Fastener Or Steel Comp 8735 Fastener Or Steel Comp 6150 Fastener Surface Treatment: Cadmium Fastener And Chromate Fastener Surface Treatment Document And Classification: Thread Series Designator: Unjf	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface Finish: Surface Finish: 63.0 Microinches Bearing Surface Of Head Material: Plastic Polyamide Locking Feature Steel Comp E4340 Fastener Or Steel Comp 4140 Fastener Or Steel Comp 8740 Fastener Or Steel Comp 8735 Fastener Or Steel Comp 6150 Fastener Surface Treatment: Cadmium Fastener And Chromate Fastener Surface Treatment Document And Classification: Thread Series Designator: Unjf	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Surface Finish: 63.0 Microinches Bearing Surface Of Head Material: Plastic Polyamide Locking Feature Steel Comp E4340 Fastener Or Steel Comp 4140 Fastener Or Steel Comp 8740 Fastener Or Steel Comp 8735 Fastener Or Steel Comp 6150 Fastener Surface Treatment: Cadmium Fastener And Chromate Fastener Surface Treatment Document And Classification: Thread Series Designator: Unjf	Surface Finish:	32.0 Microinches Grip
Material:Plastic Polyamide Locking FeatureMaterial:Steel Comp E4340 Fastener Or Steel Comp 4140 Fastener Or Steel Comp 8740 Fastener Or Steel Comp 8735 Fastener Or Steel Comp 6150 FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjf	Surface Finish:	32.0 Microinches Threads
Material: Steel Comp E4340 Fastener Or Steel Comp 4140 Fastener Or Steel Comp 8735 Fastener Or Steel Comp 8735 Fastener Or Steel Comp 6150 Fastener Surface Treatment: Cadmium Fastener And Chromate Fastener Surface Treatment Document And Classification: Thread Series Designator: Unjf	Surface Finish:	63.0 Microinches Bearing Surface Of Head
Material: Comp 6150 Fastener Cadmium Fastener And Chromate Fastener Surface Treatment Document And Classification: Classification: Thread Series Designator: Comp 6150 Fastener Cadmium Fastener And Chromate Fastener Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response Fastener Unjf	Material:	Plastic Polyamide Locking Feature
Surface Treatment Document And Classification: Oq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response Fastener Unjf	Material:	·
Classification: Classi	Surface Treatment:	Cadmium Fastener And Chromate Fastener
		Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response Fastener
Specification/standard Data: 80205-nas1224 Professional/industrial Association Standard	Thread Series Designator:	Unjf
	Specification/standard Data:	80205-nas1224 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS1224-11 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.