

## P/N NAS1224-14L

### **Description**

Fastener Length: 1-5/16", Thread: 1/4-28, Thread Length: 7/16"

\* Manufacturer certifications are shipped with your order EREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: NAS122414L

Minimum Qty (MOQ): 1 EA

NSN: 5306-01-171-2940

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS1224-14L Specifications**

Thread Direction: Right-hand  Thread Length: 0.410 Inches Minimum And 0.440 Inches Maximum  Fastener Length: 1.285 Inches Minimum And 1.315 Inches Maximum  Head Style: Dished Hexagon  Head Height: 0.125 Inches Minimum And 0.140 Inches Maximum  Width Between Flats: 0.430 Inches Minimum And 0.439 Inches Maximum  Width Between Flats: 0.430 Inches Minimum And 0.439 Inches Maximum  Grip Dameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum  Nominal Thread Diameter: 0.250 Inches  Grip Length: 0.865 Inches Minimum And 0.885 Inches Maximum  Thread Quantity Per Inch: 28  Minimum Tensile Strength: 160000 Pounds Per Square Inch  Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall  Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall  Material Document And Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6090 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Ma
Thread Length:  0.410 Inches Minimum And 0.440 Inches Maximum  Fastener Length: 1.285 Inches Minimum And 1.315 Inches Maximum  Head Style: Dished Hexagon  Head Height: 0.125 Inches Minimum And 0.140 Inches Maximum  Width Between Flats: 0.430 Inches Minimum And 0.439 Inches Maximum  Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum  Nominal Thread Diameter: 0.250 Inches  Grip Length: 0.865 Inches Minimum And 0.885 Inches Maximum  Thread Quantity Per Inch: 28  Minimum Tensile Strength: 160000 Pounds Per Square Inch  Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall  Material:  Material: 0.4000 Pounds Per Square Inch  Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Or Steel Comp 8730 Overall Or Steel Comp 8740 Overall Or Steel Comp 8750 Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Respo
Fastener Length:1.285 Inches Minimum And 1.315 Inches MaximumHead Style:Dished HexagonHead Height:0.125 Inches Minimum And 0.140 Inches MaximumWidth Between Flats:0.430 Inches Minimum And 0.439 Inches MaximumGrip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumNominal Thread Diameter:0.250 InchesGrip Length:0.865 Inches Minimum And 0.885 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec Stip Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec Stip Spec Spec Spec Spec Spec Spec Spec Spe
Head Style: Dished Hexagon  Head Height: 0.125 Inches Minimum And 0.140 Inches Maximum  Width Between Flats: 0.430 Inches Minimum And 0.439 Inches Maximum  Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum  Nominal Thread Diameter: 0.250 Inches  Grip Length: 0.865 Inches Minimum And 0.885 Inches Maximum  Thread Quantity Per Inch: 28  Minimum Tensile Strength: 160000 Pounds Per Square Inch  Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall  Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall  Material Document And Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd  Classification: Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall  Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Head Height:  0.125 Inches Minimum And 0.140 Inches Maximum  Width Between Flats: 0.430 Inches Minimum And 0.439 Inches Maximum  Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum  Nominal Thread Diameter: 0.250 Inches  Grip Length: 0.865 Inches Minimum And 0.885 Inches Maximum  Thread Quantity Per Inch: 28  Minimum Tensile Strength: 160000 Pounds Per Square Inch  Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall  Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall  Material Document And Classification:  Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall  Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Width Between Flats:  0.430 Inches Minimum And 0.439 Inches Maximum  Grip Diameter:  0.2485 Inches Minimum And 0.2495 Inches Maximum  Nominal Thread Diameter:  0.250 Inches  Grip Length:  0.865 Inches Minimum And 0.885 Inches Maximum  Thread Quantity Per Inch:  28  Minimum Tensile Strength:  160000 Pounds Per Square Inch  Hardness Rating:  36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall  Material:  Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8740 Overall  Material Document And Classification:  Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall  Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall  Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Grip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumNominal Thread Diameter:0.250 InchesGrip Length:0.865 Inches Minimum And 0.885 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rdSurface Treatment:Cadmium OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Nominal Thread Diameter:  0.250 Inches  0.865 Inches Minimum And 0.885 Inches Maximum  Thread Quantity Per Inch:  28  Minimum Tensile Strength:  160000 Pounds Per Square Inch  Hardness Rating:  36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall  Material:  Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall  Material Document And Classification:  Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall  Surface Treatment Document And Classification:  Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Grip Length:  O.865 Inches Minimum And O.885 Inches Maximum  Thread Quantity Per Inch:  28  Minimum Tensile Strength:  160000 Pounds Per Square Inch  Hardness Rating:  36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall  Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall  Material Document And  Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Classification:  Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Ove
Thread Quantity Per Inch:  Minimum Tensile Strength:  160000 Pounds Per Square Inch  Hardness Rating:  36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall  Material:  Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall  Material Document And Classification:  Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Classification:  Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall  Surface Treatment Document And Classification:  Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Minimum Tensile Strength: Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall  Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall  Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil
Hardness Rating:  36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall  Material:  Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall  Material Document And Classification:  Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall  Surface Treatment:  Cadmium Overall  Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Material:  Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall  Material Document And Classification:  Surface Treatment Document And Classification:  Surface Treatment Document And Classification:  Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall  Surface Treatment Document And Classification:  Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Material:  Material Document And  Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd  Classification:  Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall  Surface Treatment:  Cadmium Overall  Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall  Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Classification:  Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall  Surface Treatment Document And Classification:  Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall  Cadmium Overall  Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Surface Treatment Document And Classification:  Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Classification:  Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Sories Decignators Unif
Tiffead Series Designator:

# **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/shear+bolts/NAS1224-14L">https://military-fasteners.com/bolts/shear+bolts/NAS1224-14L</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/shear+bolts/NAS1224-14L">https://military-fasteners.com/bolts/shear+bolts/NAS1224-14L</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/shear+bolts/NAS1224-14L">https://military-fasteners.com/bolts/shear+bolts/NAS1224-14L</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/shear+bolts/NAS1224-14L">https://military-fasteners.com/bolts/shear+bolts/NAS1224-14L</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/shear+bolts/nas1224-14L">https://military-fasteners.com/bolts/shear+bolts/nas1224-14L</a> and selecting the quantity you want then click "add to cart".