

Description

Fastener Length: 5/8", Thread: 1/4-28, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1224C3P
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-243-3760
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1224C3P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.400 Inches Minimum And 0.450 Inches Maximum
Fastener Length:	0.598 Inches Minimum And 0.628 Inches Maximum
Head Style:	Undercut Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.178 Inches Minimum And 0.198 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	140000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Threads
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Surface Finish:	63.0 Microinches Grip
iii Part Name Assigned By Controlling Agency:	Navy Special Project
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1224 Professional/Industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1224C3P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.