

Description

Fastener Length: 1-61/64", Thread: 3/8-24, Thread Length: 19/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS122622L
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-211-9727
Schedule B:	7318.15.8085
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N NAS1226-22L Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.553 Inches Minimum And 0.603 Inches Maximum
Fastener Length:	1.938 Inches Minimum And 1.968 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.188 Inches Minimum And 0.203 Inches Maximum
Width Between Flats:	0.553 Inches Minimum And 0.564 Inches Maximum
Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	1.365 Inches Minimum And 1.385 Inches Maximum
Thread Quantity Per Inch:	24
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum Overall
Special Features:	Strip Type Element In Threads
Material:	Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 6150 Or Steel Comp 8735 Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-500 Mil Spec 2nd Material Response Or Mil-s-8503 Mil Spec 3rd Material Response Or Mil-s-6098 Mil Spec 4th Material Response Or Mil-s-6049 Mil Spec 5th Material Response Overall
Surface Treatment:	Cadmium Or Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Type 2 Class 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1226-22L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.