

**Description**

length: 5/16" diameter: 9/64", flush head, aluminum alloy, roughly 3800 pieces per pound, NAS1241 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1241AD35
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-468-5556
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



## P/N NAS1241AD3-5 Specifications

<b>Fastener Length:</b>	0.302 Inches Minimum And 0.322 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.108 Inches Minimum And 0.112 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.175 Inches Minimum And 0.183 Inches Maximum
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Part Name Assigned By Controlling Agency:</b>	Rivet-solid, 100 Degree Flush Head, Alluminum Alloy
<b>Special Features:</b>	End Item C-141 Tcas/ta;conical Surface Of The Head Shall Be Concentric With The Shank Of The Rivet Within .005;head Cocking Angle Relative To Axis Of Rivet 1/2 Degree Max;maximum Head Diameters Are To Theoretical Sharp Corners As Measured By Projection
<b>Material:</b>	Aluminum Alloy 2117 Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1241AD3-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.