

Description

length: 5/8" diameter: 9/64", solid rivet, flush head, 2117-t4 aluminum alloy, roughly 990 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS1241AD410 |
| Minimum Qty (MOQ): | 1 Pound |
| NSN: | 5320-01-504-5558 |
| ECCN: | EAR99 |



* See page 2 for technical characteristics

P/N NAS1241AD4-10 Specifications

| | |
|-----------------------------|--|
| Fastener Length: | 0.625 Inches Nominal |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.125 Inches Nominal |
| Shank Style: | Countersunk (undrilled) |
| Head Major Diameter: | 0.216 Inches Nominal |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Aluminum Alloy 5056 Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1241AD4-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.