

P/N NAS1241AD4-10

Description

length: 5/8" diameter: 9/64", solid rivet, flush head, 2117-t4 aluminum alloy, roughly 990 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1241AD410

Minimum Qty (MOQ): 1 Pound

NSN: 5320-01-504-5558

ECCN: EAR99









^{*} See page 2 for technical characteristics

P/N NAS1241AD4-10 Specifications

Fastener Length:	0.625 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.125 Inches Nominal
Shank Style:	Countersunk (undrilled)
Head Major Diameter:	0.216 Inches Nominal
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 5056 Overall

How to Order

Order this solid rivet from our inventory online by visiting https://military-fasteners.com/rivets/solid+rivets/NAS1241AD4-10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/solid+rivets/NAS1241AD4-10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/solid+rivets/NAS1241AD4-10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/solid+rivets/NAS1241AD4-10 and selecting the quantity you want then