

Description

Length: 5/16" diameter: 9/64", flush head, 2117-t4 aluminum alloy, roughly 2250 pieces per pound, NAS1241 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | NAS1241AD45 |
| Minimum Qty (MOQ): | 1 Pound |
| NSN: | 5320-01-212-9300 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |



P/N NAS1241AD4-5 Specifications

| | |
|---|--|
| Fastener Length: | 0.302 Inches Minimum And 0.322 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.140 Inches Minimum And 0.144 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.229 Inches Maximum |
| Shear Strength: | 26000 Single Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 100.5 Degrees Maximum |
| Heat Treatment: | T-4 Solution Heat Treated Overall |
| Material: | Aluminum Alloy 2117 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Or Chromate Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec 1st Treatment Response Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall |
| Specification/standard Data: | 80205-nas1241 Professional/Industrial Association Standard |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1241AD4-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.