

**Description**

length: 7/16" diameter: 9/64", flush head, 2117-t4 aluminum alloy, roughly 1675 pieces per pound, NAS1241 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1241AD47
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-375-7185
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1241AD4-7 Specifications

<b>Fastener Length:</b>	0.438 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.125 Inches Nominal
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.221 Inches Minimum And 0.229 Inches Maximum
<b>Countersink Angle:</b>	99.5 Degrees Minimum And 100.5 Degrees Maximum
<b>Special Features:</b>	Head Has Raised Teat
<b>Material:</b>	Aluminum Alloy 2117 Overall
<b>Material Document And Classification:</b>	Mil-r-5674 Mil Spec Single Material Response Overall
<b>Specification/standard Data:</b>	80205-nas1241 Professional/industrial Association Standard

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1241AD4-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.