

Description

length: 3/4" diameter: 11/64", solid rivet, flush head, 2117-t4 aluminum alloy, roughly 537 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1241AD512
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-616-7733
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS1241AD5-12 Specifications

Fastener Length:	0.750 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.250 Inches Nominal
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.476 Inches Nominal
Countersink Angle:	100.0 Degrees Nominal
Part Name Assigned By Controlling Agency:	Rivet, Solid 100 Deg Flush Head
Heat Treatment:	T-4 Solution Heat Treated Body
Material:	Aluminum Alloy 2117 Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1241AD5-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.