

**Description**

length: 1/4" diameter: 11/64", solid rivet, flush head, 2117-t4 aluminum alloy, roughly 1640 pieces per pound

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1241AD54
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-622-5596
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N NAS1241AD5-4 Specifications

<b>Fastener Length:</b>	0.250 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.171 Inches Minimum And 0.175 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.282 Inches Minimum And 0.290 Inches Maximum
<b>Grip Length:</b>	0.141 Inches Nominal
<b>Countersink Angle:</b>	99.5 Degrees Minimum And 100.5 Degrees Maximum
<b>iii Part Name Assigned By Controlling Agency:</b>	Solid Rivet- Universal Head
<b>Special Features:</b>	Head Is Dimpled 0.020 Max. Depth X 0.030 Max Width
<b>Material:</b>	Aluminum Alloy 2117 Overall
<b>Specification/standard Data:</b>	80205-nas1241ad5-4 Professional/industrial Association Standard

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1241AD5-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.