

Description

length: 1/4" diameter: 11/64", solid rivet, flush head, 2117-t4 aluminum alloy, roughly 1640 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1241AD54
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-622-5596
ECCN:	EAR99



P/N NAS1241AD5-4 Specifications

Fastener Length:	0.250 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.171 Inches Minimum And 0.175 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.282 Inches Minimum And 0.290 Inches Maximum
Grip Length:	0.141 Inches Nominal
Countersink Angle:	99.5 Degrees Minimum And 100.5 Degrees Maximum
iii Part Name Assigned By Controlling Agency:	Solid Rivet- Universal Head
Special Features:	Head Is Dimpled 0.020 Max. Depth X 0.030 Max Width
Material:	Aluminum Alloy 2117 Overall
Specification/standard Data:	80205-nas1241ad5-4 Professional/industrial Association Standard

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1241AD5-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.