

Description

length: 5/16" diameter: 11/64", solid rivet - 100°, flush head - 2117-t4 aluminum alloy

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1241AD55 |
| Minimum Qty (MOQ): | 1 Pound |
| NSN: | 5320-01-370-6388 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

P/N NAS1241AD5-5 Specifications

| | |
|-----------------------------|--|
| Fastener Length: | 0.302 Inches Minimum And 0.322 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.171 Inches Minimum And 0.175 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.282 Inches Minimum And 0.290 Inches Maximum |
| Grip Length: | 0.078 Nominal Inches |
| Countersink Angle: | 99.5 Degrees Minimum And 100.5 Degrees Maximum |
| Special Features: | Head Is Dimpled 0.020 Max. |
| Material: | Aluminum Alloy 2117 Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1241AD5-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.