

**Description**

length: 1/2" diameter: 7/32", solid rivet - 100°, flush head - 2117-t4 aluminum alloy

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1241AD68
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-412-0872
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE  
AVAILABLE

## P/N NAS1241AD6-8 Specifications

<b>Fastener Length:</b>	0.490 Inches Minimum And 0.510 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.188 Inches Nominal
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.353 Inches Nominal
<b>Countersink Angle:</b>	95.0 Degrees Minimum And 100.5 Degrees Maximum
<b>Material:</b>	Aluminum Alloy 2117 Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1241AD6-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.