

Description

Fastener Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1241AD812
Minimum Qty (MOQ):	20 EA
NSN:	5320-01-434-0520
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1241AD8-12 Specifications

Fastener Length:	0.740 Inches Minimum And 0.760 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.280 Inches Minimum And 0.284 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.472 Inches Minimum And 0.480 Inches Maximum
Countersink Angle:	99.5 Degrees Minimum And 100.5 Degrees Maximum
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1241 Professional/Industrial Association Standard

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1241AD8-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.