

**Description**

Fastener Length: 3/4"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1241B612                               |
| Minimum Qty (MOQ):      | 145 EA                                    |
| NSN:                    | 5320-01-434-0527                          |
| Schedule B:             | 7616.10.3000                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1241B6-12 Specifications

|   |  |
|---|--|
| <b>Fastener Length:</b>                               | 0.740 Inches Minimum And 0.760 Inches Maximum                                  |
| <b>Head Style:</b>                                    | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| <b>Shank Diameter:</b>                                | 0.171 Inches Minimum And 0.175 Inches Maximum                                  |
| <b>Shank Style:</b>                                   | Straight W/radius Chamfered Tip  |
| <b>Head Major Diameter:</b>                           | 0.282 Inches Minimum And 0.290 Inches Maximum                                  |
| <b>Countersink Angle:</b>                             | 99.5 Degrees Minimum And 100.5 Degrees Maximum                                 |
| <b>Material:</b>                                      | Aluminum Alloy 5056 Overall  |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Overall                             |
| <b>Surface Treatment:</b>                             | Anodize Overall  |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625 Mil Spec Single Treatment Response Overall                          |
| <b>Specification/standard Data:</b>                   | 80205-nas1241 Professional/Industrial Association Standard                     |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1241B6-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.