

**Description**

Fastener Length: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | NAS1241D55          |
| Minimum Qty (MOQ):      | 500 EA              |
| NSN:                    | 5320-01-248-7818    |
| Schedule B:             | 7616.10.3000        |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE  
AVAILABLE

## P/N NAS1241D5-5 Specifications

|   |  |
|---|--|
| <b>Fastener Length:</b>                               | 0.302 Inches Minimum And 0.322 Inches Maximum  |
| <b>Head Style:</b>                                    | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)                           |
| <b>Shank Diameter:</b>                                | 0.171 Inches Minimum And 0.175 Inches Maximum  |
| <b>Shank Style:</b>                                   | Straight W/radius Chamfered Tip  |
| <b>Head Major Diameter:</b>                           | 0.290 Inches Maximum   |
| <b>Shear Strength:</b>                                | 33000 Single Pounds Per Square Inch  |
| <b>Countersink Angle:</b>                             | 99.5 Degrees Minimum And 100.5 Degrees Maximum   |
| <b>Heat Treatment:</b>                                | T-4 Solution Heat Treated Overall  |
| <b>Material:</b>                                      | Aluminum Alloy 2017 Overall  |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Overall   |
| <b>Surface Treatment:</b>                             | Anodize Overall Or Chromate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall |
| <b>Specification/standard Data:</b>                   | 80205-nas1241 Professional/industrial Association Standard   |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1241D5-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.