

Description

Fastener Length: 7/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS1241D614 |
| Minimum Qty (MOQ): | 20 EA |
| NSN: | 5320-01-434-0545 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1241D6-14 Specifications

| | |
|---|--|
| Fastener Length: | 0.865 Inches Minimum And 0.885 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.218 Inches Minimum And 0.222 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.349 Inches Minimum And 0.357 Inches Maximum |
| Countersink Angle: | 99.5 Degrees Minimum And 100.5 Degrees Maximum |
| Material: | Aluminum Alloy 2017 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1241 Professional/Industrial Association Standard |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1241D6-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.