

Description

Fastener Length: 1-1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1241DD612
Minimum Qty (MOQ):	50 EA
NSN:	5320-01-500-8571
Schedule B:	7616.10.3000
ECCN:	9A991



NO IMAGE
AVAILABLE

P/N NAS1241DD6-12 Specifications

Fastener Length:	1.250 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.187 Inches Nominal
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.480 Inches Maximum
Shear Strength:	33000 Single Pounds Per Square Inch
Countersink Angle:	99.5 Degrees Minimum And 100.5 Degrees Maximum
Material:	Aluminum Alloy 2024 Overall
Surface Treatment:	Anodize Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1241DD6-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.