

**Description**

Fastener Length: 7/8", NAS1241 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1241DD614
Minimum Qty (MOQ):	10
NSN:	5320-01-500-8567
Schedule B:	7616.10.3000
ECCN:	EAR99

NO IMAGE  
AVAILABLE

## P/N NAS1241DD6-14 Specifications

<b>Fastener Length:</b>	0.875 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.1875 Inches Nominal
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.349 Inches Minimum And 0.357 Inches Maximum
<b>Shear Strength:</b>	330000 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	99.5 Degrees Minimum And 100.5 Degrees Maximum
<b>Material:</b>	Aluminum Alloy 2024 Overall
<b>Surface Treatment:</b>	Anodize Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1241DD6-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.