

Description

length: 3/4" diameter: 9/64", solid rivet - universal head - 2117-t4 aluminum alloy

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1242AD412
Minimum Qty (MOQ):	100
NSN:	5320-01-616-7731



\* See page 2 for technical characteristics

## P/N NAS1242AD4-12 Specifications

<b>Fastener Length:</b>	0.740 Inches Minimum And 0.760 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.140 Inches Minimum And 0.144 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Tapered, Threaded
<b>Head Major Diameter:</b>	0.221 Inches Minimum And 0.229 Inches Maximum
<b>Tip Diameter:</b>	0.140 Inches Minimum And 0.144 Inches Maximum
<b>Countersink Angle:</b>	99.500 Degrees Minimum And 100.500 Degrees Maximum
<b>Material:</b>	Aluminum Alloy 2117 Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1242AD4-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.