

Description

length: 3/4" diameter: 9/64", solid rivet - universal head - 2117-t4 aluminum alloy

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1242AD412
Minimum Qty (MOQ):	100
NSN:	5320-01-616-7731



P/N NAS1242AD4-12 Specifications

Fastener Length:	0.740 Inches Minimum And 0.760 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.140 Inches Minimum And 0.144 Inches Maximum
Shank Style:	Pin-rivet, Tapered, Threaded
Head Major Diameter:	0.221 Inches Minimum And 0.229 Inches Maximum
Tip Diameter:	0.140 Inches Minimum And 0.144 Inches Maximum
Countersink Angle:	99.500 Degrees Minimum And 100.500 Degrees Maximum
Material:	Aluminum Alloy 2117 Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1242AD4-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.