

Description

length: 1" diameter: 11/64", solid rivet - universal head, aluminum alloy, roughly 565 pieces per pound, NAS1242 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1242AD416
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-238-7855
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



P/N NAS1242AD4-16 Specifications

Fastener Length:	0.990 Inches Minimum And 1.010 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.139 Inches Minimum And 0.143 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Shear Strength:	26000 Single Pounds Per Square Inch
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall Or Oxide Film Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall
Specification/standard Data:	80205-nas1242 Professional/industrial Association Standard

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1242AD4-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.