

Description

length: 1/4" diameter: 9/64", universal head, aluminum alloy, roughly 2,060 pieces per pound, NAS1242 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------------------|
| SKU / Model: | NAS1242AD44 |
| Minimum Qty (MOQ): | 1 Pound |
| NSN: | 5320-01-339-5971 |
| ECCN: | EAR99 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |



P/N NAS1242AD4-4 Specifications

| | |
|-------------------------------------------------------|----------------------------------------------------------------------------------------------------------|
| Fastener Length: | 0.240 Inches Minimum And 0.260 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.054 Inches Minimum And 0.064 Inches Maximum |
| Shank Diameter: | 0.139 Inches Minimum And 0.143 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.238 Inches Minimum And 0.262 Inches Maximum |
| Shear Strength: | 26000 Single Pounds Per Square Inch |
| Material: | Aluminum Alloy 2117 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall Or Chromate Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall |
| Specification/standard Data: | 80205-nas1242 Professional/industrial Association Standard |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1242AD4-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.