

# P/N NAS1242AD4-5

### **Description**

length: 5/16" diameter: 9/64", universal head, aluminum alloy, roughly 1420 pieces per pound, NAS1242 series rivet

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1242AD45

Minimum Qty (MOQ): 1 Pound

NSN: 5320-01-622-5799

ECCN: EAR99









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1242AD4-5 Specifications

Fastener Length:	0.312 Inches Nominal
Head Style:	Brazier
Shank Diameter:	0.125 Inches Nominal
Shank Style:	Straight W/radius Chamfered Tip
Minimum Tensile Strength:	26000 Pounds Per Square Inch
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Ms20470 Assn Std 1st Material Response Or Ms20426 Assn Std 2nd Material Response Overall

# **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/NAS1242AD4-5">https://military-fasteners.com/rivets/solid+rivets/NAS1242AD4-5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/NAS1242AD4-5">https://military-fasteners.com/rivets/solid+rivets/NAS1242AD4-5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/NAS1242AD4-5">https://military-fasteners.com/rivets/solid+rivets/NAS1242AD4-5</a> and selecting the quantity you want then click "add to cart".