

P/N NAS1242AD4-8

Description

length: 1/2" diameter: 9/64", solid rivet, universal head, 2117-t4 aluminum alloy

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: NAS1242AD48

Minimum Qty (MOQ): 100

NSN: 5320-01-422-4364

ECCN: EAR99

National Motor Freight: 096320, Rivets I / S Nickel Plated Buffed







^{*} See page 2 for technical characteristics

P/N NAS1242AD4-8 Specifications

Fastener Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.140 Inches Nominal
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Material:	Aluminum Alloy 2117 Overall

How to Order

Order this solid rivet from our inventory online by visiting https://military-fasteners.com/rivets/solid+rivets/NAS1242AD4-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/solid+rivets/NAS1242AD4-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/solid+rivets/NAS1242AD4-8 and selecting the quantity you want then click "add to cart".