

Description

length: 3/4" diameter: 11/64", universal head, 2117-t4 aluminum alloy, roughly 470 pieces per pound, NAS1242 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1242AD512
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-616-7729
Schedule B:	7616.10.3000
ECCN:	EAR99



P/N NAS1242AD5-12 Specifications

Fastener Length:	0.740 Inches Minimum And 0.760 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.171 Inches Minimum And 0.176 Inches Maximum
Shank Style:	Pin-rivet, Tapered, Threaded
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Tip Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Countersink Angle:	99.500 Degrees Minimum And 100.500 Degrees Maximum
Material:	Aluminum Alloy 2117 Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1242AD5-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.