

**Description**

length: 3/4" diameter: 11/64", universal head, 2117-t4 aluminum alloy, roughly 470 pieces per pound, NAS1242 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1242AD512
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-616-7729
Schedule B:	7616.10.3000
ECCN:	EAR99



## P/N NAS1242AD5-12 Specifications

<b>Fastener Length:</b>	0.740 Inches Minimum And 0.760 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Head Height:</b>	0.067 Inches Minimum And 0.077 Inches Maximum
<b>Shank Diameter:</b>	0.171 Inches Minimum And 0.176 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Tapered, Threaded
<b>Head Major Diameter:</b>	0.296 Inches Minimum And 0.328 Inches Maximum
<b>Tip Diameter:</b>	0.296 Inches Minimum And 0.328 Inches Maximum
<b>Countersink Angle:</b>	99.500 Degrees Minimum And 100.500 Degrees Maximum
<b>Material:</b>	Aluminum Alloy 2117 Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1242AD5-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.