

Description

length: 1/4" diameter: 11/64", universal head, 2117-t4 aluminum alloy, roughly 1000 pieces per pound, NAS1242 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1242AD54
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-622-4848
Schedule B:	7616.10.3000
ECCN:	EAR99



P/N NAS1242AD5-4 Specifications

Fastener Length:	0.250 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.156 Inches Nominal
Minimum Tensile Strength:	26000 Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Ms20470 Assn Std 1st Material Response Or Ms20426 Assn Std 2nd Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1242AD5-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.