

Description

length: 1/4" diameter: 11/64", universal head, 2117-t4 aluminum alloy, roughly 1000 pieces per pound, NAS1242 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS1242AD54 |
| Minimum Qty (MOQ): | 1 Pound |
| NSN: | 5320-01-622-4848 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |



P/N NAS1242AD5-4 Specifications

| | |
|--|--|
| Fastener Length: | 0.250 Inches Nominal |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.156 Inches Nominal |
| Minimum Tensile Strength: | 26000 Pounds Per Square Inch |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Aluminum Alloy 2117 Overall |
| Material Document And Classification: | Ms20470 Assn Std 1st Material Response Or Ms20426 Assn Std 2nd Material Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1242AD5-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.