

Description

Length: 5/16" diameter: 11/64", universal head, 2117-t4 aluminum alloy, roughly 870 pieces per pound, NAS1242 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1242AD55
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-305-7606
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N NAS1242AD5-5 Specifications

Fastener Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.171 Inches Minimum And 0.176 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Shear Strength:	26000 Single Pounds Per Square Inch
Heat Treatment:	T-4 Solution Heat Treated Overall
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430,t4 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall Or Chromate Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1242AD5-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.