

Description

length: 1/2" diameter: 7/32", universal head, aluminum alloy

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[MS20470AD7-8](#)

| | |
|-------------------------|---------------------|
| SKU / Model: | NAS1242AD68 |
| Minimum Qty (MOQ): | 1 Pound |
| NSN: | 5320-00-301-8567 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |



* See page 2 for technical characteristics

P/N NAS1242AD6-8 Specifications

| | |
|---|--|
| Fastener Length: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.093 Inches Minimum And 0.103 Inches Maximum |
| Shank Diameter: | 0.218 Inches Minimum And 0.223 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.415 Inches Minimum And 0.459 Inches Maximum |
| Shear Strength: | 26000 Single Pounds Per Square Inch |
| Heat Treatment: | T-4 Solution Heat Treated Overall |
| Material: | Aluminum Alloy 2117 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall Or Oxide Film Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1242AD6-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.