

Description

Fastener Length: 7/16", roughly 735 pieces per pound, NAS1242 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1242D57 |
| Minimum Qty (MOQ): | 200 |
| NSN: | 5320-01-249-0503 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |

NO IMAGE
AVAILABLE

P/N NAS1242D5-7 Specifications

| | |
|---|--|
| Fastener Length: | 0.428 Inches Minimum And 0.448 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.080 Inches Minimum And 0.090 Inches Maximum |
| Shank Diameter: | 0.171 Inches Minimum And 0.176 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.296 Inches Minimum And 0.328 Inches Maximum |
| Shear Strength: | 33000 Single Pounds Per Square Inch |
| Heat Treatment: | T-4 Solution Heat Treated Overall |
| Material: | Aluminum Alloy 2017 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall Or Chromate Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall |
| Specification/standard Data: | 80205-nas1242 Professional/industrial Association Standard |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/NAS1242D5-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.