

**Description**

Thread: 5/16-24, Thread Length: 5/8

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS125120
Minimum Qty (MOQ):	1
NSN:	5306-00-987-9913
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS1251-2-0 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.602 Inches Minimum And 0.662 Inches Maximum
<b>Shank Length:</b>	0.632 Inches Nominal
<b>Nominal Thread Diameter:</b>	0.3125 Inches
<b>Thread Quantity Per Inch:</b>	24
<b>Material:</b>	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall Or Zinc Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 2 Class 3 Fed Spec 1st Treatment Response Overall Or Qq-z-325 Type 2 Class 3 Fed Spec 2nd Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1251-2-0> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.