

Description

Thread: 5/16-24, Thread Length: 5/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS125120
Minimum Qty (MOQ):	1
NSN:	5306-00-987-9913
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1251-2-0 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.602 Inches Minimum And 0.662 Inches Maximum
Shank Length:	0.632 Inches Nominal
Nominal Thread Diameter:	0.3125 Inches
Thread Quantity Per Inch:	24
Material:	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Surface Treatment:	Cadmium Overall Or Zinc Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2 Class 3 Fed Spec 1st Treatment Response Overall Or Qq-z-325 Type 2 Class 3 Fed Spec 2nd Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1251-2-0> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.