

Description

Hole Diameter: 1/4", Diameter: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS125210LC
Minimum Qty (MOQ):	75 EA
NSN:	5310-01-409-0175



* See page 2 for technical characteristics

P/N NAS1252-10LC Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.193 Inches Minimum And 0.213 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Thickness:	0.028 Inches Minimum And 0.036 Inches Maximum
Overall Diameter:	0.433 Inches Minimum And 0.458 Inches Maximum
Material:	Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-250/12 Fed Spec Single Material Response Overall
Surface Treatment:	Chromate Overall
Surface Treatment Document And Classification:	Mil-c-5541, Cl 3 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1252 Professional/industrial Association Standard

How to Order

Order this washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1252-10LC> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.