

Description

Hole Diameter: 7/8", Diameter: 1-1/2", Thickness: 1/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS12521416H
Minimum Qty (MOQ):	35 EA
NSN:	5310-01-004-0886
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



* See page 2 for technical characteristics

P/N NAS1252-1416H Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.880 Inches Minimum And 0.900 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Thickness:	0.057 Inches Minimum And 0.069 Inches Maximum
Overall Diameter:	1.495 Inches Minimum And 1.520 Inches Maximum
Material:	Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-250/12 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Ty 2 Cl 1 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1252 Professional/Industrial Association Standard

How to Order

Order this washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1252-1416H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.