

Description

Hole Diameter: 7/8", Diameter: 1-1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS12521416L |
| Minimum Qty (MOQ): | 20 EA |
| NSN: | 5310-01-242-0678 |
| National Motor Freight: | 194120, Washers / Gaskets / Pckg Dvcs Noi |

NO IMAGE
AVAILABLE

P/N NAS1252-1416L Specifications

| | |
|---|---|
| Cross-sectional Shape Style: | Rectangular |
| Hole Diameter: | 0.880 Inches Minimum And 0.900 Inches Maximum |
| Peripheral Shape Style: | Round |
| Center Hole Shape Style: | 1 Round |
| Thickness: | 0.028 Inches Minimum And 0.036 Inches Maximum |
| Overall Diameter: | 1.495 Inches Minimum And 1.520 Inches Maximum |
| Color: | Yellow Overall |
| Material: | Aluminum Alloy 7075 Overall |
| Material Document And Classification: | Qq-a-250/12,t6 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625,ty 2 Cl 2 Mil Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1252 Professional/Industrial Association Standard |

How to Order

Order this washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1252-1416L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.