

Description

Diameter: 1-3/4", Thickness: 1/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS12521616H
Minimum Qty (MOQ):	25
NSN:	5310-00-277-9338
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



NO IMAGE
AVAILABLE

P/N NAS1252-1616H Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	1.005 Inches Minimum And 1.025 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Center Hole Shape Style:	Round
Thickness:	0.057 Inches Minimum And 0.069 Inches Maximum
Overall Diameter:	1.745 Inches Minimum And 1.770 Inches Maximum
Special Features:	Dyed Yellow
Material:	Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-250/12,t4 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,type 2 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1252 Professional/Industrial Association Standard

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1252-1616H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.