

P/N NAS1252-2016L

Description

Hole Diameter: 1-17/64", Diameter: 2", Thickness: 1/32"

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: NAS12522016L

Minimum Qty (MOQ): 45 EA

NSN: 5310-01-369-8924



^{*} See page 2 for technical characteristics

P/N NAS1252-2016L Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	1.255 Inches Minimum And 1.275 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Thickness:	0.028 Inches Minimum And 0.036 Inches Maximum
Overall Diameter:	1.995 Inches Minimum And 2.020 Inches Maximum
Material:	Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-250/12,t6 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall And Chromate Overall
Surface Treatment Document And Classification:	Mil-a-8625,type 2 Cl 2 Mil Spec 1st Treatment Response Overall And Mil-c-5541,cl 3 Mil Spec 2nd Treatment Response Overall

How to Order

Order this washer from our inventory online by visiting https://military-fasteners.com/washers/flat+washers/NAS1252-2016L and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/washers/flat+washers/NAS1252-2016L and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/washers/flat+washers/NAS1252-2016L and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/washers/flat+washers/NAS1252-2016L and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/washers/<a href="http