

**Description**

Hole Diameter: 1-17/64", Diameter: 2", Thickness: 1/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS12522016L
Minimum Qty (MOQ):	45 EA
NSN:	5310-01-369-8924



\* See page 2 for technical characteristics

## P/N NAS1252-2016L Specifications

<b>Cross-sectional Shape Style:</b>	Rectangular
<b>Hole Diameter:</b>	1.255 Inches Minimum And 1.275 Inches Maximum
<b>Peripheral Shape Style:</b>	Round
<b>Center Hole Shape Style:</b>	1 Round
<b>Thickness:</b>	0.028 Inches Minimum And 0.036 Inches Maximum
<b>Overall Diameter:</b>	1.995 Inches Minimum And 2.020 Inches Maximum
<b>Material:</b>	Aluminum Alloy 7075 Overall
<b>Material Document And Classification:</b>	Qq-a-250/12,t6 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625,type 2 Cl 2 Mil Spec 1st Treatment Response Overall And Mil-c-5541,cl 3 Mil Spec 2nd Treatment Response Overall

## How to Order

Order this washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1252-2016L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.