

**Description**

Hole Diameter: 1-17/64", Diameter: 2", Thickness: 1/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | NAS12522016L     |
| Minimum Qty (MOQ): | 45 EA            |
| NSN:               | 5310-01-369-8924 |



## P/N NAS1252-2016L Specifications

|   |  |
|---|--|
| <b>Cross-sectional Shape Style:</b>                   | Rectangular  |
| <b>Hole Diameter:</b>                                 | 1.255 Inches Minimum And 1.275 Inches Maximum  |
| <b>Peripheral Shape Style:</b>                        | Round  |
| <b>Center Hole Shape Style:</b>                       | 1 Round  |
| <b>Thickness:</b>                                     | 0.028 Inches Minimum And 0.036 Inches Maximum  |
| <b>Overall Diameter:</b>                              | 1.995 Inches Minimum And 2.020 Inches Maximum  |
| <b>Material:</b>                                      | Aluminum Alloy 7075 Overall  |
| <b>Material Document And Classification:</b>          | Qq-a-250/12,t6 Fed Spec Single Material Response Overall   |
| <b>Surface Treatment:</b>                             | Anodize Overall And Chromate Overall   |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625,type 2 Cl 2 Mil Spec 1st Treatment Response Overall And Mil-c-5541,cl 3 Mil Spec 2nd Treatment Response Overall |

## How to Order

Order this washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1252-2016L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.