

## P/N NAS1252-3016L

### **Description**

Hole Diameter: 1-7/8", Diameter: 2-5/8"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS12523016L

Minimum Qty (MOQ): 10 EA

NSN: 5310-01-352-4412

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1252-3016L Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	1.880 Inches Minimum And 1.900 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Thickness:	0.028 Inches Minimum And 0.036 Inches Maximum
Overall Diameter:	2.620 Inches Minimum And 2.645 Inches Maximum
Material:	Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-250/12,t6 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1252 Professional/industrial Association Standard

## **How to Order**

Order this washer from our inventory online by visiting <a href="https://military-fasteners.com/washers/flat+washers/NAS1252-3016L">https://military-fasteners.com/washers/flat+washers/NAS1252-3016L</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.