

Description

Size: 1/4" thickness 0.032", 7075-t6 aluminum alloy, NAS1252 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1252416L
Minimum Qty (MOQ):	100
NSN:	5310-00-961-8433
Schedule B:	7616.10.8000
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



* See page 2 for technical characteristics

P/N NAS1252-416L Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.255 Inches Minimum And 0.275 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Thickness:	0.028 Inches Minimum And 0.036 Inches Maximum
Overall Diameter:	0.495 Inches Minimum And 0.520 Inches Maximum
Material:	Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-250/12,temper T6 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 2,cl 1 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1252 Professional/Industrial Association Standard

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1252-416L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.