

Description

size: #4 thickness 0.032", flat washer - 7075-t6 aluminum alloy

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS12524L
Minimum Qty (MOQ):	100
NSN:	5310-00-450-1902
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi

NO IMAGE
AVAILABLE

P/N NAS1252-4L Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.115 Inches Minimum And 0.135 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Center Hole Shape Style:	Round
Thickness:	0.028 Inches Minimum And 0.036 Inches Maximum
Overall Diameter:	0.307 Inches Minimum And 0.332 Inches Maximum
Material:	Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-250/12 T6 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Ty 2 Cl 1 Mil Spec Single Treatment Response Overall

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1252-4L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.