

Description


Hole Diameter: 29/64", Diameter: 49/64", Thickness: 1/32", NAS1252 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1252716L
Minimum Qty (MOQ):	100
NSN:	5310-00-851-7746
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



P/N NAS1252-716L Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.443 Inches Minimum And 0.463 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Thickness:	0.028 Inches Minimum And 0.036 Inches Maximum
Overall Diameter:	0.745 Inches Minimum And 0.770 Inches Maximum
Criticality Code Justification:	Matt
Material:	Aluminum Alloy 6061 Overall
Material Document And Classification:	Qq-a-250/11 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Type 2 Mil Spec Single Treatment Response Overall

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1252-716L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.