

Description

Hole Diameter: 29/64", Diameter: 49/64", Thickness: 1/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1252716LC
Minimum Qty (MOQ):	1000 EA
NSN:	5310-01-501-2158
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



* See page 2 for technical characteristics

P/N NAS1252-716LC Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.443 Inches Minimum And 0.463 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Thickness:	0.032 Inches Nominal
Overall Diameter:	0.745 Inches Minimum And 0.770 Inches Maximum
End Item Identification:	Hydraulic Installation Ldg Gear Misc Sec Pwr Misc
Part Name Assigned By Controlling Agency:	Washer- 7075 Aluminum Alloy Flat
Material:	Aluminum Alloy Overall
Material Document And Classification:	Qq-a-250/12 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Type II, Class 2 (yellow) Mil Spec Single Treatment Response Overall

How to Order

Order this washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS1252-716LC> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.